

## INFORMATION

# OIL AID-OA-10

OIL GELLANT ACTIVATOR

### DESCRIPTION

OIL AID-OA-10 is a stabilized liquid activator for use in conjunction with OIL AID-OG-10 in Messina's OIL AID GELLED OIL SYSTEM. Its properties are:

Form	Water White Liquid
Specific Gravity, 60° F	1.46
Pour Point	- 40 °F
Flash Point	200 °F
Viscosity at 60° F	154.5 cps
pH (5% sol)	12.7
Charge	Nonionic

### APPLICATION

OIL AID-OA-10 is a stabilized inorganic liquid which acts as an activator for the oil gellant OIL AID-OG-10. OIL AID-OA-10 can be used in conjunction with OIL AID-OG-10 in crude oils ranging in gravity from 30° (API) to very high gravity condensates.

The OIL AID GELLED OIL SYSTEM will gel kerosene and diesel oil, as well as blends of crude oils with these solvents.

### RECOMMENDED TREATMENT

The normal dosage of OIL AID-OA-10 is 1.35 gal for every 10 gal of OIL AID-OG-10. In order to achieve maximum viscosity, however, it will be necessary to check each formation crude to determine the proper dosage of OIL AID-OA-10 and OIL AID-OG-10.

### HANDLING

OIL AID-OA-10 should be handled as a strong alkali since it causes burns if splashed on the skin or in the eyes. Wear goggles or a face shield when handling. Do not take OIL AID-OA-10 internally.

### PACKAGING

OIL AID-OA-10 is available in 55-gallon steel drums.

OIL AID-OA-10 is a Messina trademark