

## INFORMATION

# OIL AID-WG-50

## WATER GELLANT

### DESCRIPTION

OIL AID-WG-50 is a fast hydrating, organic type gelling agent. OIL AID-WG-50 is compatible with most well stimulation agents.

### APPLICATION

OIL AID-WG-50 can be used in fresh water, brackish water, seawater and saturated salt fluids. OIL AID-WG-50 is effective when the well application temperature range is 100° F (38° C) to 225° F (107° C).

OIL AID-WG-50 also acts as an effective friction reducer.

### RECOMMENDED TREATMENT

Recommendations for a mixing program should be made only after a complete well history has been obtained and a thorough study made of all the factors affecting the stimulation problem.

Normal use concentrations of OIL AID-WG-50 are 10-110 lb per 1,000 U.S. gal.

### HANDLING

OIL AID-WG-50 is essentially non-toxic but inhalation and skin contact may cause irritation. Remove to fresh air or wash exposed area with soap and water. Goggles should be worn while handling. Dust is an eye irritant and may cause eye injury.

In case of eye contact, flush with large amounts of water for 15 minutes. If irritation persists, seek medical attention.

### PACKAGING

OIL AID-WG-50 is packaged in export quality 50 lb or 25 kg net bags.

OIL AID-WG-50 is a Messina trademark