

INFORMATION

OLAID-CI-206

OIL-SOLUBLE CORROSION INHIBITOR

DESCRIPTION

OILAID-CI-206 is an oil-soluble corrosion inhibitor that forms a tenacious film which protects against corrosion due to hydrogen sulfide, carbon dioxide, and saline solutions. Its typical properties are.

Form Liquid
Specific Gravity 0.963
Flash Point > 150 °F

Solubility Soluble in Water, TEA, DEA, Soluble in Crude

Oil, Dispersible in Diesel, Insoluble in Water

Viscosity at 150 °C 200 to 300 cPs

APPLICATION

OILAID-CI-206 is designed to provide a tough, long lasting protective film, not only in the primary working parts of a well, but throughout crude gathering lines, storage tanks, and pipelines.

RECOMMENDED TREATMENT

OILAID-CI-206 is intended to be used continuously in a dosage range of 5 to 25 ppm depending upon the severity of the corrosion environment and the protection desired.

HANDLING

Avoid prolonged exposure or inhalation of the vapor of OILAID-CI-206. Use in a well ventilated area. Avoid contact with eyes, skin and clothing. In case of contact with skin or eyes, flush with large quantities of water. In the case of eye contact, if irritation persists, seek medical attention. Remove contaminated clothing immediately and wash before re-use.

PACKAGING

OILAID-CI-206 is available in 55 gallon drums.

OILAID-CI-206 is a Messina trademark